

STATE OF KANSAS
BASE VEHICLE
SPECIFICATIONS
FOR
PICKUP TRUCK 1/2 TON

ENGINE: Minimum of six cylinders with a minimum displacement of 3.7 L.

WHEEL BASE: Minimum of 133".

G.V.W.: The gross vehicle weight shall be a minimum of 6,100 pounds.

BODY: To be standard cab with eight (8) foot, styleside or fleetside type pickup body. Exterior and interior to be custom trimmed with single, standard, factory color.

BUMPERS: Front to be painted or chrome oval type. Rear to be factory installed, "step" type with single license tag light and holes for trailer ball and safety chain.

TRANSMISSION: To be automatic type with not less than three (3) speeds forward and one reverse.

REAR AXLE: To be standard for engine and transmission, specified above, used for normal highway use.

BRAKES: To be hydraulic, front disc, rear drum or disc with vacuum power assist.

TIRES: Sized and load rated by manufacturer's recommendations for G.V.W. specified. All season tread.

SPARE TIRE: Fullsize Tire and rim to be furnished with side mounted carrier inside truck bed or under bed.

FUEL TANK: To be standard frame mounted. 26 gallon capacity.

STEERING: Power assisted.

RADIO: AM/FM.

WINDSHIELD, REAR WINDOW & SIDE GLASS: To be tinted.

MIRRORS: One inside prismatic day-night type and right and left outside below eyeline rear view mirrors. (Minimum 40 sq. inches).

INSTRUMENTS STANDARD DASH: Temperature gauge, oil pressure gauge, voltmeter gauge and fuel gauge.

AIR CONDITIONER: Fresh air type, factory installed.

WINDSHIELD WIPERS: Intermittent with washer.

AIR BAGS: Driver and front passenger.